



# NITROPOWER DERINGER

Hybrid design that combines dynamism and strength

## ○ Spec

Product Name	DERINGER
Size	16inch / 17inch / 18inch / 20inch
Construction Method	Cast 1 piece wheel Made in China
Safety Standards	6H-139.7 JWL(800KG) JWL-T(955KG) / 5H-114.3 JWL(690KG) VIA compliant
Color	BLACK METALLIC POLISH / BLACK CLEAR / FLANGE PIERCE DRILLED(BMA) SEMIGLOSS BLACK POLISH / FLANGE PIERCE DRILLED(SBK) SEMIGLOSS BLACK / FLANGE PIERCE DRILLED(SBM)
Included	Center cap, valve
Optional	Center cap (S type for 114.3-5H) ¥3,000 Center cap (L type for 139.7-6H) ¥3,000 Air Valve ¥800



BLACK METALLIC POLISH / BLACK CLEAR / FLANGE PIERCE DRILLED (BMA) (20×8.5J)



BLACK METALLIC POLISH / BLACK CLEAR / FLANGE PIERCE DRILLED (BMA)(18×7.0J)



SEMIGLOSS BLACK POLISH / FLANGE PIERCE DRILLED(SBM) (20×8.5J)

Prices are noted in Japanese YEN(JPY). Specifications in the English version are intended for customers outside of Japan and do not include Japan sales tax.

SIZE	INSET ( ): HUB CLEARANCE ( mm )	HOLE	P.C.D.	HUB BORE ( φ )	DRILL ( φ )	PRICE		
						SBK	BMA	SBM
<b>16x6.5J</b>	38(35)	6	139.7	106.1	29-13	49,000	50,000	-
<b>16x7J</b>	40(42)	5	114.3	73.1	29-13	51,000	-	52,000
<b>17x6.5J</b>	48(30)	6	139.7	100	29-13	57,000	-	58,000
	38(40)			106.1		-	58,000	-
<b>17x7J</b>	42(42)	5	114.3	73.1	29-13	59,000	60,000	60,000
<b>17x8J</b>	20(35)	6	139.7	106.1	29-13	-	64,000	-
<b>18x7J</b>	42(42)	5	114.3	73.1	29-13	69,000	-	-
<b>20x8.5J</b>	20(42)	6	139.7	106.1	29-13	-	84,000	-

Caution

This product has the disc protruding beyond the rim depending on the size, so please take care when installing