



NITROPOWER

CROSS CLAW

Combines powerful spokes and deep rim style

○ Spec

Product Name	CROSS CLAW
Size	15inch / 16inch / 17inch
Construction Method	Cast 1 pc. wheel (16×5.5J 16×6.0J is reverse rim) Made in China
Safety Standards	5H-114.3 JWL(690KG) VIA compliant 6H-139.7 JWL(800KG) JWL-T(955KG) VIA compliant 5H-139.7 JWL(620KG) JWL-T(700KG) VIA compliant
Color	Black metallic + Mirror Cut(BMM) Semiloss Black + Pierce Drilled(SBK)
Included	Center cap (except 16×5.5J 16×6.0J), valve
Optional	Center cap (except 16×5.5J 16×6.0J) ¥3,000 Air valve ¥800



BLACK METALLIC + MIRROR CUT(BMM) (17×8.0J)



SEMI GLOSS BLACK + PIERCE DRILLED (SBK)(17×8.0J)



BLACK METALLIC + MIRROR CUT(BMM)

Prices are noted in Japanese YEN(JPY). Specifications in the English version are intended for customers outside of Japan and do not include Japan sales tax.

SIZE	RIM	INSET (): HUB CLEARANCE (mm)	HOLE	P.C.D.	HUB BORE (φ)	DRILL (φ)	PRICE	
							BMM	SBK
15x6J	27mm	33(35)	6	139.7	106.1	29-15	41,000	41,000
16x5.5J	50mm	20	5	139.7	108.1	29-15	45,000	-
16x6J	62mm	-5	5	139.7	108.8	29-15	46,000	46,000
16x6.5J	38mm	48(30)	6	139.7	106.1	29-15	47,000	-
		38(40)						47,000
17x6.5J	38mm	48(30)	6	139.7	106.1	29-15	55,000	-
		38(40)						55,000
17x7J	28mm	40(45)	5	114.3	73.1	29-15	57,000	-
17x8J	46mm	20(43)	6	139.7	106.1	29-15	61,000	-

-